

TR 128 - Technical Specifications



Description

TR 128 has been specially designed for utility tractors and rototillers. The wide and deep lug design and the special cut-and-chip resistance compound provide an extended tire service life. TR 128 features maximum traction on wet soil.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Rototiller, Universal Vehicle

Version	STANDARD
Type	TT
Tyre Size	5 - 12
LI/SS	64 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	127
Overall Diameter (mm)	554
Static Loaded Radius (mm)	265
Rolling Circumference (mm)	1638
Rim Rec	4 JA
ECE	E11-106R-005189

Load capacity (Kg)

km/h / bar	3.50
30	280

Printed on 06/04/2022 12:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

