

AW 909 - Technical Specifications



Description AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement

machinery, trailers and balers. It is ideal for modern

farming both on and off the road.

UM International Standard

Construction BIAS

Machinery Agriculture: Baler, Implement Machinery, Trailer

Version STANDARD

Type TT

Tyre Size 11.5/80 - 15.3

Dimensions International Standard

Ply Rating	16
Section Width (mm)	297
Overall Diameter (mm)	844
Static Loaded Radius (mm)	370
Rolling Circumference (mm)	2473
Rim Rec	9.00

Load capacity (Kg)

km/h / bar	5.40
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575

Printed on 25/09/2020 12:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without

