

RDR 75

A powerful open shoulder drive tire that delivers uncompromised grip, higher mileage, improved tread

and casing life in heavy-duty regional/urban truck applications.



TIRE SIZE	PLY RATING/ LOAD RANGE	LI / SI	MEAS. RIM (IN.)	MAX. OVERALL DIA (IN./MM)	MAX. OVERALL WIDTH (IN./MM)	TREAD DEPTH (32"/MM)	MAX TIRE LOAD SINGLE (LBS@PSI / KG@KPA)	MAX TIRE LOAD DUAL (LBS@PSI / KG@KPA)
215/75R17.5	16H	128/126M	6	30.7 779	8.7 220	16 12.5	3970@110 1800@750	3750@110 1700@750
235/75R17.5	16H	132/130M	6.75	31.9 811	9.5 242	17 13	4410@112 2000@775	4190@112 1900@775
245/70R17.5	16H	134/132M	7.5	32.6 827	10.2 258	17 13	4675@112 2120@775	4410@112 2000@775
265/70R17.5	16H	140/138M	7.5	32.7 831	10.7 272	17 13.5	5510@830 2500@830	5201@830 2360@830
295/60R22.5	18J	150/147K	9	37 940	12 304	20 16	7390@130 3350@900	6780@130 3075@900
275/80R22.5	16H	149/146M	8.25	40.6 1030	11.3 287	25 20	7160@120 3250@830	6610@120 3000@830
295/80R22.5	18J	152/148M	9	41.8 1062	12.2 310	25 20	7830@123 3550@850	6940@123 3150@850
315/60R22.5	20L	150/147K	9.75	38 966	12.8 326	20 16	7383@130 3350@900	6777@130 3075@900
315/70R22.5	18J	154/150L	9	40.6 1032	12.5 318	25 19.5	8270@130 3750@900	7390@130 3350@900
315/80R22.5	18J	156/150L	9	43.1 1096	12.5 318	26 20.5	8820@123 4000@850	7390@123 3350@850