

RMR 61

It's a versatile, all position tire for regional/urban applications. Enhanced braking power, comfort, driving control, wet grip and uniform wear make it a perfect fit for multi-position roles, from steer to trailer.



TIRE SIZE	PLY RATING/ LOAD RANGE	LI / SI	MEAS. RIM (IN.)	MAX. OVERALL DIA (IN./MM)	MAX. OVERALL WIDTH (IN./MM)	TREAD DEPTH (32"/MM)	MAX TIRE LOAD SINGLE (LBS@PSI / KG@KPA)	MAX TIRE LOAD DUAL (LBS@PSI / KG@KPA)
215/75R17.5	16H	128/126M	6	30.7 779	8.7 220	14 11.5	3970@110 1800@750	3750@110 1700@750
235/75R17.5	18J	132/130M	6	31.9 811	9.5 242	15 12	4410@112 2000@775	4190@112 1900@775
245/70R17.5	18J	134/132M	7.5	32.6 827	10.2 258	15 12	4675@112 2120@775	4410@112 2000@775
265/70R17.5	16H	140/138M	7.5	32.7 831	10.7 272	15 12	5510@830 2500@830	5201@830 2360@830
275/80R22.5	16H	149/146M	8.25	40.6 1030	11.3 287	21 16.5	7160@120 3250@830	6610@120 3000@830
295/60R22.5	18J	150/147L	9	37 940	12 304	17 13.8	7160@120 3250@830	5201@830 2360@830
295/80R22.5	18J	154/149M	9	41.8 1062	12.2 310	21 16.5	8270@123 3750@850	7160@123 3250@850
315/80R22.5	18J	156/150L	9	43.1 1096	12.5 318	22 17.5	8820@123 4000@850	7390@123 3350@850
315/70R22.5	18J	156/150L	9	40.6 1032	12.5 318	20 15.5	8820@130 4000@900	7390@130 3350@900
385/55R22.5	20L	160K	12.25	39.8 1012	15.8 401	19 15	9918@130 4500@900	- -
385/65R22.5	20L	164K	11.75	43 1092	15.9 405	19 15	11000@130 5000@900	- -
13R22.5	18J	156/150K	9.75	45.1 1146	12.8 326	22 17.5	8820@125 4000@860	7390@125 3350@860