

RTR 61

Radial for closed and spread axle regional trailers that provides an optimum balance of extended mileage and even tread

wear for an uninterrupted and comfortable ride. Its reinforced casing protects the tire from curb damage.



TIRE SIZE	PLY RATING/ LOAD RANGE	LI / SI	MEAS. RIM (IN.)	MAX. OVERALL DIA (IN./MM)	MAX. OVERALL WIDTH (IN./MM)	TREAD DEPTH (32"/MM)	MAX TIRE LOAD SINGLE (LBS@PSI / KG@KPA)	MAX TIRE LOAD DUAL (LBS@PSI / KG@KPA)
215/75R17.5	16J	128/126K	6	30.7 779	8.7 220	13 10.5	3970@110 1800@750	3750@110 1700@750
235/75R17.5	18J	132/130M	6.75	31.9 811	9.5 242	14 11	4410@112 2000@775	4190@112 1900@775
245/70R17.5	16H	143/141M	6.75	31.9 811	9.5 242	14 11	6005@127 2725@875	5675@127 2575@875
385/55R22.5	20L	160K	12.25	39.8 1012	15.8 401	19 15.5	9918@130 4500@900	- -
385/65R22.5	20L	164K	11.75	43 1092	15.9 405	20 16	11000@130 5000@900	- -