

## AGRIMAX RT 657 - Technical Specifications



### Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

### UM

International Standard

### Construction

RADIAL

### Machinery

Agriculture: Tractor, Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	650/65 R 42
LI/SS	165 D/168 A8

### Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1913
Static Loaded Radius (mm)	878
Rolling Circumference (mm)	5853
Rim Rec	DW 20 B
ECE	E4-106R-000625
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2475	2885	3245	3605	3970	4275	4740	5150
50	2600	3030	3410	3790	4170	4495	4980	5410
40	2690	3140	3530	3920	4315	4650	5155	5600
30	2845	3320	3735	4150	4565	4920	5455	5925
10 LT	3315	3870	4355	4835	5320	5735	6355	6905
10 HT	2845	3320	3735	4150	4565	4920	5455	5925

Printed on 22/09/2020 10:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..